



MAXUS

Deliver 9



VAN FWD/RWD N1 3.5T / N2 4.0T

VERSION	L2H2	
	FWD (SRW)	RWD (SRW)
DIMENSIONS		
Seating	3	3
Slide door	Single/Dual	Single/Dual
Overall length (mm)	5546	5546
Overall width without mirrors (mm)	2062	2062
Overall height (mm)	2555	2555
Wheelbase (mm)	3366	3366
Maximum load volume (with bulkhead) (cu.m)	10.2	9.7
WEIGHTS AND PAYLOAD		
GVM(kg)	3500	3800
Min.kerb mass (kg)*	2210	2350
Max.gross payload (kg)	1290	1450
GTM (kg)	6000	6000
Max.towing (Braked/Unbraked) (kg)	2800/750	2800/750
PERFORMANCE AND STEERING		
Peak power (kW)	120	130
Peak torque (Nm)	375	420
Max speed (km/h)	160	155
Min.turning circle (m)	12.9	12.9
ENGINE AND TRANSMISSION		
Engine	D20T	D20T
Displacement (ml)	1996	1996
Fuel	Diesel	Diesel
Emission level	EURO 5 /EURO 6	EURO 6 /EURO VI
Transmission	6MT	6MT/8AT
WHEELS AND TYRES		
Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Single Rear Wheel
Tyres	215/75R16	235/65R16

VAN FWD/RWD N1 3.5T / N2 4.0T

VERSION	L3H2	
	FWD (SRW)	RWD (SRW)
DIMENSIONS		
Seating	3	3
Slide door	Single/Dual	Single/Dual
Overall length (mm)	5940	5940
Overall width without mirrors (mm)	2062	2062
Overall height (mm)	2535	2535
Wheelbase (mm)	3760	3760
Maximum load volume (with bulkhead) (cu.m)	11.5	11
WEIGHTS AND PAYLOAD		
GVM(kg)	3500	3500/4000
Min.kerb mass (kg)*	2285	2360/2400
Max.gross payload (kg)	1215	1140/1600
GTM (kg)	6000	6000
Max.towing (Braked/Unbraked) (kg)	2800/750	2800/750
PERFORMANCE AND STEERING		
Peak power (kW)	110~130	110~130
Peak torque (Nm)	375~420	375~420
Max speed (km/h)	160	145
Min.turning circle (m)	14.1	14.1
ENGINE AND TRANSMISSION		
Engine	D20T	D20T
Displacement (ml)	1996	1996
Fuel	Diesel	Diesel
Emission level	EURO 5 /EURO 6/EURO VI	EURO 6 /EURO VI
Transmission	6MT	6MT/8AT
WHEELS AND TYRES		
Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Single Rear Wheel
Tyres	215/75R16	235/65R16

VAN FWD/RWD N1 3.5T / N2 4.0T

VERSION	L3H3	
	FWD (SRW)	RWD (SRW)
DIMENSIONS		
Seating	3	3
Slide door	Single/Dual	Single/Dual
Overall length (mm)	5940	5940
Overall width without mirrors (mm)	2062	2062
Overall height (mm)	2755	2755
Wheelbase (mm)	3760	3760
Maximum load volume (with bulkhead) (cu.m)	12.9	12.3
WEIGHTS AND PAYLOAD		
GVM(kg)	3500	3500/4000
Min.kerb mass (kg)*	2300	2390/2420
Max.gross payload (kg)	1200	1110/1580
GTM (kg)	6000	6000
Max.towing (Braked/Unbraked) (kg)	2800/750	2800/750
PERFORMANCE AND STEERING		
Peak power (kW)	110~130	110~130
Peak torque (Nm)	375~420	375~420
Max speed (km/h)	160	140
Min.turning circle (m)	14.1	14.1
ENGINE AND TRANSMISSION		
Engine	D20T	D20T
Displacement (ml)	1996	1996
Fuel	Diesel	Diesel
Emission level	EURO 6 /EURO VI	EURO 6 /EURO VI
Transmission	6MT	6MT/8AT
WHEELS AND TYRES		
Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Single Rear Wheel
Tyres	215/75R16	235/65R16

SINGLE CHASSIS CAB N1 3.5T / N2 4.5T

VERSION	L3H0	
	RWD (SRW)	RWD (DRW)

DIMENSIONS

Seating	3	3
Overall length (mm)	6200	6200
Overall width without mirrors (mm)	2052	2094
Overall height (mm)	2320	2320
Wheelbase (mm)	3760	3760

WEIGHTS AND PAYLOAD

GVM(kg)	3500	3500/4495
Min.kerb mass (kg)*	1980	2050/2110
Max.gross payload (kg)	1520	1450/2385
GTM (kg)	6000	6000
Max.towing (Braked/Unbraked) (kg)	2800/750	2800/750

PERFORMANCE AND STEERING

Peak power (kW)	110~130	110~130
Peak torque (Nm)	375~420	375~420
Max speed (km/h)	145	145
Min.turning circle (m)	14.1	14.1

ENGINE AND TRANSMISSION

Engine	D20T	D20T
Displacement (ml)	1996	1996
Fuel	Diesel	Diesel
Emission level	EURO VI	EURO VI
Transmission	6MT	6MT/8AT

WHEELS AND TYRES

Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Dual Rear Wheel
Tyres	235/65R16	195/75R16

SINGLE CHASSIS CAB N1 3.5T / N2 4.5T

VERSION	L4H0	
	RWD (SRW)	RWD (DRW)
DIMENSIONS		
Seating	3	3
Overall length (mm)	6680	6680
Overall width without mirrors (mm)	2052	2094
Overall height (mm)	2320	2320
Wheelbase (mm)	4048	4048
WEIGHTS AND PAYLOAD		
GVM(kg)	3500	3500/4495
Min.kerb mass (kg)*	2010	2080/2140
Max.gross payload (kg)	1490	1420/2355
GTM (kg)	6000	6000
Max.towing (Braked/Unbraked) (kg)	2800/750	2800/750
PERFORMANCE AND STEERING		
Peak power (kW)	110~130	110~130
Peak torque (Nm)	375~420	375~420
Max speed (km/h)	145	145
Min.turning circle (m)	15.2	15.2
ENGINE AND TRANSMISSION		
Engine	D20T	D20T
Displacement (ml)	1996	1996
Fuel	Diesel	Diesel
Emission level	EURO VI	EURO VI
Transmission	6MT	6MT/8AT
WHEELS AND TYRES		
Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Dual Rear Wheel
Tyres	235/65R16	195/75R16

MINIBUS M2 3.8T / 4.05T

VERSION	L2H2	L3H2	L3H3
	RWD (SRW)	RWD (SRW)	RWD (SRW)

DIMENSIONS

Seating	11~13	12~16	12~16
Slide door	Single	Single	Single
Overall length (mm)	5546	5940	5940
Overall width without mirrors (mm)	2062	2062	2062
Overall height (mm)	2525	2545	2740
Wheelbase (mm)	3366	3760	3760

WEIGHTS AND PAYLOAD

GVM(kg)	3800	4050	4050
Min.kerb mass (kg)*	2550~2600	2700~2780	2725~2800

PERFORMANCE AND STEERING

Peak power (kW)	110~130	110~130	110~130
Peak torque (Nm)	375~420	375~420	375~420
Max speed (km/h)	155	155	150
Min.turning circle (m)	12.9	14.1	14.1

ENGINE AND TRANSMISSION

Engine	D20T	D20T	D20T
Displacement (ml)	1996	1996	1996
Fuel	Diesel	Diesel	Diesel
Emission level	EURO V/EURO VI	EURO V/EURO VI	EURO V/EURO VI
Transmission	6MT/8AT	6MT/8AT	6MT/8AT

WHEELS AND TYRES

Wheels	16-inch steel/alloy wheel	16-inch steel/alloy wheel	16-inch steel/alloy wheel
Rear wheels	Single Rear Wheel	Single Rear Wheel	Single Rear Wheel
Tyres	235/65R16	235/65R16	235/65R16

*It is the weight of a standard-specification base vehicle (different series will have different kerb masses) without the driver (75 kg), crew or cargo.